



[CODENAME]

EXPLORER NATURAL

LRC



95 | 105 | 105 HD | 115 | 125



SAME

EXPLORER NATURAL

TECHNICAL DATA

		95	105	105 HD	115	125
ENGINE						
Model		FARMotion				
Emission level		LRC				
Cylinders/Displacement	n°/cc	4/3849				
Bore/Stroke	mm	103/115.5				
Aspiration		Turbo Intercooler				
Injection @ pressure	Type	Common Rail @ 2000 bar				
Max. power @ 2000 rpm	kW/HP	71/97		78/106	85/116	93/126
Rated power @ 2200 rpm	kW/HP	57.3/92		74/101	80.6/110	88/120
Max. power @ 1600 rpm	Nm	386		425	462	508
Torque rise	%			32		31
Visco cooling fan				▲		
Standard cooling fan				○		-
Fuel tank	l			145		
TRANSMISSION						
SDF transmission	Type	T4330		T4350		T5350
Gearbox	n°	5 gears x 2 or 4 ranges				
MECHANICAL SHUTTLE						
Shuttle	Type	Mechanical with lever under steering wheel				
N° of speed (4 ranges)	n°	20+20				
N° of speed with Hi-Lo (2 ranges)	n°	20+20 Hi-Lo				
N° of speed with Hi-Lo (4 ranges)	n°	40+40 Hi-Lo				
HYDRAULIC SHUTTLE						
PowerShuttle	Type	Hydraulic with lever under steering wheel				
Adjust. response of PowerShuttle		5 different setting				
N° of speed (4 ranges)	n°	20+20				
N° of speed with Hi-Lo (2 ranges)	n°	20+20 Hi-Lo				
N° of speed with Hi-Lo (4 ranges)	n°	40+40 Hi-Lo				
Stop&Go		▲				
ComfortClutch		▲				
PTO						
Electrohydraulic engagement				▲		
540/540ECO			▲			-
540/540ECO/1000/1000ECO			-			▲
LIFT						
Mechanical rear lift			▲			-
Mechanical rear lift with EasyLift			○			-
Electronic rear lift			-			▲
Rear lifting capacity (STD)	kg			3600		
Rear lifting capacity (OPT)	kg		4525			5410
HYDRAULICS						
Pump flow	l/min			55		
Rear spool valves	n°		2/3			3
BRAKES						
4 wheel braking				▲		
Mechanical parking brake				▲		
Hydraulic trailer brake				○		
FRONT AXLE						
Front axle	Size	1.5			2	
Steering angle	degrees	50			55	
Electrohydraulic 4WD engagement				▲		
Electrohydraulic Diff. Lock engagement				▲		
CAB						
4 pillar cab				▲		
Standard roof				▲		
High visibility roof				○		
High visibility roof - FOPS				○		
Hydro Silent-Block suspension				▲		
Manual A/C				▲		
Mechanical suspended seat			▲			-
Pneumatic suspended seat			○			▲
DELUXE pneum. suspended seat				○		
Passenger seat			○			▲
External controls for PTO and lift			○			▲
Radio				▲		
DIMENSIONS AND WEIGHTS						
Wheelbase	mm	2400				
Max. length	mm	4268				
Centre rear axle - cab	mm	1968				
Weight	kg	4000		4250		4350
Front admissible load	kg	2900			3000	
Rear admissible load	kg	3700		4000		5000
Total admissible load	kg	6500		7000		7500

▲ STD ○ OPT - Not available

Models and options may vary depending on the market. Please contact your dealer/distributor for more information.



To find out more, visit same-tractors.com or talk to your dealer.

SAME is a brand of SDF

The technical data and images contained herein are indicative only. SAME reserves the right to modify its products at any time without prior notice. Cod. 308.9013.3.1-0 - 07/2024