



[ CODENAME ]

# FRUTTETO<sup>PRO</sup>

■ STAGE V

90 | 95 | 100 | 105 | 115

90 | 95 | 100 | 105 | 115



**SAME**

		FRUTTETO <sup>PRO</sup> S/V				
		90	95	100	105	115
<b>ENGINE</b>						
Model		FARMotion 35	FARMotion 45	FARMotion 35	FARMotion 45	
Emission level		Stage V				
Aspiration		Turbo Intercooler				
Injection @ pressure	Type	Common Rail @ 2000 bar				
Cylinders/Displacement	n°/cc	3/2887	4/3849	3/2887	4/3849	
Max. power (ECE R120)	kW/HP	67/91	70/95	75/102	78/106	85/116
Power at rated speed (ECE R120)	kW/HP	63.5/86	66.4/90	71.1/97	74/101	80.6/110
Max. torque @ 1400 rpm	Nm	372	389	417	433	472
XL Fuel tank capacity (with front lift/PTO)	l	100 (80)				
Fuel tank for narrow mid-mounted implement installation on Frutteto <sup>PRO</sup> S capacity (with front lift/PTO)	l	-	73 (53)	-	73 (53)	
AdBlue tank capacity	l	13				
<b>TRANSMISSION - POWERSHUTTLE</b>						
PowerShuttle with SenseClutch, Stop&Go, ComfortClutch		▲				
Number of speed - 5 gears transmission		30+30 (with Hi-Lo 2-Powershift steps) or 45+45 (with HML 3-Powershift steps)				
Max. speed	km/h	40 ECO**				
<b>PTO</b>						
PTO speeds		540/540ECO or 540/540ECO/1000 or 540/540ECO/Ground Speed				
Rear Auto PTO function		▲				
Front PTO 1000		○				
<b>LIFT</b>						
Electronic rear lift		▲				
Vibration damping function		▲				
Rear linkage lifting capacity - Frutteto <sup>PRO</sup> (STD/OPT)	kg	3130/3940				
Rear linkage lifting capacity - Frutteto <sup>PRO</sup> S	kg	2600				
Rear linkage lifting capacity - Frutteto <sup>PRO</sup> V	kg	2600				
Hydraulic right tie rod and stabilizers		○				
Front lift (2100 kg)		○				
<b>HYDRAULICS</b>						
Hydraulic flow	l/min	88				
Independent steering pump	l/min	42				
Rear spool valves with electronic control (STD/OPT)	n°	3/4				
Rear free return		▲				
Mid-mounted spool valves with electronic control (OPT)	n°	2/4				
Mid-mounted duplicated ways (OPT)	n°	2/3/5/8				
Mid-mounted free returns (OPT)		1/2				
<b>BRAKES</b>						
Front axle with brakes		▲				
Hydraulic trailer brake		○				
ABS Socket		○				
<b>FRONT AXLE</b>						
Electrohydraulic engagement for 4WD and Diff.Lock		▲				
Auto 4WD		○				
Steering Double Displacement (SDD)		○				
<b>ACTIVEDRIVE FRONT SUSPENDED AXLE (OPT)</b>						
Adaptive-Damping, Active Self-Leveling functions		▲				
Anti-Dive, Anti-Roll functions		▲				
Differential Traction Control (DTC)		▲				
<b>CAB</b>						
4 pillar cab		▲				
Flat floor		▲				
InfoCentre*		▲				
Electronic joystick with spool valves swappable controls		▲				
Jolly buttons		▲				
Adjustable steering column		▲				
Suspended on Hydro Silent-Block		▲				
Cat.4 filtration system		○				
Liftable rear top roof		▲				
Rounded top windscreen		▲				
Openable front windscreen		○				
Halogen working lights (STD)	n°	4				
LED working lights (OPT)	n°	4/6/8				
Smartphone holder and 2 USB plugs		▲				
Radio		○				
Jump start		○				
External controls for PTO and lift		▲				
<b>SDF SMART FARMING SOLUTIONS</b>						
CTM - Telematics module		▲*				
iMonitor		○				
ISOBUS		○				
ROWguidance prearrangement		○				

\*in EU-28

\*\*on FRUTTETO<sup>PRO</sup>/FRUTTETO<sup>PRO</sup> S/FRUTTETO<sup>PRO</sup> V 40 kph

FRUTTETO <sup>PRO</sup>		90	95	100	105	115
DIMENSIONS AND WEIGHTS						
With front tyre	Size	300/70 R20				
With rear tyre	Size	420/70 R28				
Wheelbase	mm	2044	2174	2044	2174	
Max. length	mm	3850	3980	3850	3980	
Total height - CAB	mm	2520				
Height at bonnet	mm	1475				
Width	mm	1624				
Weight	kg	3290-3880	3515-4105	3290-3880	3515-4105	
Total admissible load	kg	5200				

FRUTTETO <sup>PRO S</sup>		90	95	100	105	115
DIMENSIONS AND WEIGHTS						
With front tyre	Size	280/70 R18				
With rear tyre	Size	380/70 R28				
Wheelbase	mm	2086	2216	2086	2216	
Max. length	mm	3860	3990	3860	3990	
Total height - CAB	mm	2495				
Height at bonnet	mm	1475				
Width	mm	1380				
Weight	kg	3265-3865	3320-3920	3265-3865	3320-3920	
Total admissible load	kg	5000				

FRUTTETO <sup>PRO V</sup>		90	95	100	105	115
DIMENSIONS AND WEIGHTS						
With front tyre	Size	180/95 R16				
With rear tyre	Size	280/85 R24				
Wheelbase	mm	2086	2216	2086	2216	
Max. length	mm	3860	3990	3860	3990	
Total height - CAB	mm	2395				
Height at bonnet	mm	1440				
Width	mm	1166				
Weight	kg	3180-3690	3235-3745	3180-3690	3235-3745	
Total admissible load	kg	5000				

- ▲ STD
- OPT
- not available



### NEW HYDRAULIC SYSTEM

- Up to 4 rear electrohydraulic spool valves and 1 free return
- Up to 4 mid-mounted electrohydraulic spool valves and 2 free returns
- Up to 8 mid-mounted hydraulics ways
- Possibility to manage all spool valves with 1 joystick
- 88 l/ min oil flow
- Electronic rear lift

### SDF SMART FARMING SOLUTIONS

- ROWguidance prearrangement
- CTM connectivity
- iMonitor
- ISOBUS

### CAB

- InfoCentre\* cluster
- Hydro Silent-Block suspension
- Cat.4 filtration and pressurisation system
- Flat floor and no central tunnel
- Adjustable steering column
- Jolly buttons and jolly thumbwheel

### AXLES

- Fixed front axle or ActiveDrive
- True 4-wheel braking
- SDD and Auto4WD function available

### FARMOTION 35 AND 45

- FARMotion 35 and 45 engines, 3 and 4 cyl
- FARMotion 45 features the highest displacement in the segment
- FARMotion 35 allows short wheelbase for high maneuverability
- Max. power up to 116 HP
- Tapered and sloping bonnet gives excellent agility and visibility
- HVO ready

### TRANSMISSION

- Powershift transmission with Hi-Lo (30+30 speeds) or HML (45+45 speeds)
- PowerShuttle with new lever
- Stop&Go and ComfortClutch and SenseClutch functions
- Max speed 40 km/h at eco engine speeds

The technical data and images contained herein are indicative only. SAME reserves the right to modify its products at any time without prior notice.  
Cod. 308.9024.3.1-0 - 11/2024

To find out more, visit [same-tractors.com](http://same-tractors.com) or talk to your dealer.



SAME is a brand of SDF



# SAME